

RANGES	Michelin name for competition tyres	Equivalent metric size + load and speed index	Ext. dia. (mm)	Rolling circumference (mm)	Recommended ETRTO rim widths (inches)	Cross-section/ Rim (mm/inches)	Average cross-section widths measured in mm, at 1.8 bar and at 25°C															
							5" Rims	5,5" Rims	6" Rims	6,5" Rims	7" Rims	7,5" Rims	8" Rims	8,5" Rims	9" Rims	9,5" Rims	10" Rims	10,5" Rims	11" Rims			
<b>TB5+</b>	16/53-13 TB5+ F	185/55 R 13 72 V	533	1677	5 à 6,5	-	178,08	183,08	188,28	193,28												
	16/53-13 TB5+ R	185/55 R 13 72 V	533	1677	5 à 6,5	-	178,08	183,08	188,28	193,28												
	20/53-13 TB5+ F	245/40 R 13 77 V	528	1659	8 à 9,5	-						237,88	243,08	248,08	253,28							
	20/53-13 TB5+ R	245/40 R 13 77 V	528	1659	8 à 9,5	-						237,88	243,08	248,08	253,28							
	18/60-15 TB5+ F	225/50 R 15 79 V	608	1912	6 à 8	-			212,78	217,78	222,98	227,98	232,98									
	23/59-15 TB5+R	265/40 R 15 92 W	592	1817	8,5 à 10	-																
	23/62-15 TB5+ F	275/45 R 15 86 W	622	1957	8,5 à 10,5	-								266,8	271,8	277	282	287				
	23/62-15 TB5+ R	275/45 R 15 86 W	622	1957	8,5 à 10,5	-								266,8	271,8	277	282	287				
	26/61-15 TB5+ F	285/40 R 15 87 W	611	1920	9,5 à 11	-										283,63	288,63	293,63	298,83			
29/61-15 TB5+R	335/35 R 15 93 W	616	1890	11 à 13	-																	
<b>TB5</b>	16/53 - 13 TB 5 F	185/55 R 13 72 V	531	1625	5 à 6,5	195 / 6																
	20/53 - 13 TB 5 F	245/40 R 13 77 V	531	1625	8 à 9,5	252 / 9																
	18/60 - 15 TB 5 F	225/50 R 15 79 V	605	1857	6 à 8	230 / 7																
	18/60 - 15 TB 5 R	225/50 R 15 79 W	605	1857	6 à 8	230 / 7																
	23/62 - 15 TB 5 F	275/45 R 15 86 W	620	1903	8,5 à 10,5	278 / 9																
	23/62 - 15 TB 5 R	275/45 R 15 86 W	620	1903	8,5 à 10,5	278 / 9																
	23/59 - 15 TB 5 R	265/40 R 15 92 W	592	1817	8,5 à 10,5	269 / 9																
	26/61 - 15 TB 5 F	285/40 R 15 87 W	610	1871	9,5 à 11	291 / 10																
	26/61 - 15 TB 5 R	285/40 R 15 87 W	610	1871	9,5 à 11	291 / 10																
29/61 - 15 TB 5 R	335/35 R 15 93 W	616	1890	11 à 13	341 / 11,5																	
<b>TB 15 (MIXED) PB 20 (MAXI-RAIN)</b>	16/53 - 13 TB15	175/60 R 13 72 V	536	1640	5 à 6	189 / 6																
	20/53 - 13 TB15	225/45 R 13 77 V	533	1635	7 à 8,5	231 / 8																
	15/60 - 15 TB 15	170/65 R 15 77 V	601	1847	5 à 6	185 / 6																
	18/60 - 15 TB 15	215/55 R 15 79 V	612	1885	6 à 7,5	224 / 7																
	23/62 - 15 TB 15	270/45 R 15 86 V	625	1923	8,5 à 10,5	268 / 9																
	26/61 - 15 TB 15	295/40 R 15 87 V	615	1891	10 à 11,5	288 / 10																
	29/61 - 15 TB 15	335/35 R 15 93 V	621	1903	11 à 13	330 / 11,5																
	18/60 - 15 PB 20	205/55 R 15 79 H	609	1869	5,5 à 7,5	220 / 6,5																
	23/62 - 15 PB 20	275/45 R 15 86 H	628	1928	8,5 à 10,5	266 / 9																

## MICHELIN HISTORIC COMPETITION

### TECHNICAL SPECIFICATIONS

⚠ The technical data contained in this document is given for information purposes only. Checks must be carried out under real conditions.

